

InfiniStreamNG 9700 Appliance

HIGHLIGHTS

- Provides storage capacity of 64TB per appliance
 - Extend storage capacity up to 192TB with 2-64TB ESUs
 - Supports NETSCOUT's suite of Service Assurance applications
-

InfiniStreamNG Platform Overview

The InfiniStreamNG™ platform represents the next evolution of NETSCOUT's high capacity and flexible appliances that leverage Adaptive Service Intelligence™ (ASI) technology to perform deep packet capture and analysis of services, service enablers and network performance. Offering unsurpassed scalability, InfiniStreamNG probes are integrated with the nGeniusONE® Service Assurance platform to provide a common set of packet-flow-based metadata for use in troubleshooting, service and application performance, detailed key performance indicators, as well as real-time and historical forensic analysis. NETSCOUT offers multiple InfiniStreamNG models (appliance, COTS-based software and virtual appliances) to support the different processing and storage needs of enterprise and service provider environments including business services, mobile, fixed-line voice, residential triple-play, satellite and cable/MSO networks.

InfiniStreamNG 9700 Overview

InfiniStreamNG 9700 appliances are ideal for high capacity 10 Gigabit monitoring in data centers, high-volume aggregation links and service provider environments that require vast storage for long-term, historical forensic analysis. With an impressive storage capacity that begins at 64TB, InfiniStreamNG 9700 probes can be extended all the way to 192TB per appliance using up to 2-64TB Extended Storage Units (ESU).

Deployment

Strategically deployed throughout the network, InfiniStreamNG 9700 appliances provide superior processing power, packet capture and data storage appropriate for high-volume traffic found in the core of large enterprises and data centers. InfiniStreamNG 9700 appliances present real-time views of end-to-end call trace data and network-wide KPI visibility, to protect the reliability and availability of networks and services.



9795 | 64TB up to 192TB, 4 Port 10 GbE SFP+
ESU | 64TB, Extended Storage Unit

SPECIFICATIONS

InfiniStreamNG 9700 Appliance

Packet Capture Ports	4 Port 1/10 GbE SFP/SFP+
Management Port	Four onboard Fast/Gigabit/10 Gigabit Ethernet LAN ports (eth0 used for management) One dedicated 1-Gigabit IPMI port for remote management
Storage	64TB to 192TB with up to 2-64TB ESUs (RAID 6)
Embedded OS	Solid State Drive (SSD) dedicated to Linux® OS
Rack Unit	3 Rack Unit (3RU)
Dimensions	5.2 in (132 mm) Height 17.2 in (437 mm) Width 25.5 in (648 mm) Depth
Weight	82 lbs (37.19 kg)
Mounts	Rack mount side rails included
Power Rating (AC)	1+1 hot-swappable, redundant, 1000W, auto-ranging, 100VAC, 50-60 Hz, 12A 240VAC, 50-60 Hz, 4A
Maximum Consumption (AC)	7.2A, 736W
Heat Dissipation (AC)	2511 BTU/hr
Power Rating (DC)	-48VDC/1000W 24A (x2) 1+1 hot-swappable
Maximum Consumption (DC)	18A, 851W
Heat Dissipation (DC)	2904 BTU/hr
Vibration	0.75G at 5-200 Hz
Operating Temperature	50° to 95°F (10° to 35°C)
Operating Humidity	8% - 90% (non-condensing)
Altitude	-45 to 9,500 ft (-13.7m to 2,896 m)
Mechanical Shock	1 shock pulse up to 40G for up to 2ms
Regulatory Approvals	Regulatory Model Number: V4, FCC Part 15 Class A, CE Mark (EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3), VCCI (Japan) Class A, RRA (Korea) KC Cert #: KCC-REM-NSZ-V4 UL 60950-1, CAN/CSA C22.2 No. 60950, IEC 60950-1, EN 60950-1, CB Report, UL-GS (DEMKO)

SPECIFICATIONS

ESU (Extended Storage Unit)

Storage	64TB (RAID 6)
Rack Unit	3 Rack Unit (3RU)
Dimensions	5.2 in (132 mm) Height 17.2 in (437 mm) Width 25.5 in (648 mm) Depth
Weight	70.35 lbs (31.91 kg)
Mounts	Rack mount side rails included
Power Rating (AC)	hot-swappable, redundant, 900W, auto-ranging 100VAC, 50-60 Hz, 12A 240VAC, 50-60 Hz, 4A
Maximum Consumption (AC)	2A, 235W
Heat Dissipation (AC)	802 BTU/Hr
Power Rating (DC)	850W, -48VDC, (2x) 24 Amp, hot-swappable, redundant
Maximum Consumption (DC)	5A, 240W
Heat Dissipation (DC)	819 BTU/Hr
Vibration	0.75G at 5-200 Hz
Operating Temperature	50° to 95°F (10° to 35°C)
Operating Humidity	8% - 90% (non-condensing)
Altitude	-45 to 9,500 ft (-13.7m to 2,896 m)
Mechanical Shock	1 shock pulse up to 40G for up to 2ms
Regulatory Approvals	Regulatory Model Number: V3JBD, FCC Part 15 Class A, CE Mark (EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3), VCCI (Japan) Class A, RRA (Korea) KC Cert #: KCC- REM-NSZ-V3JBD UL 60950-1, CAN/CSA C22.2 No. 60950, IEC 60950-1, EN 60950-1, CB Report, UL- GS (DEMKO)

nGeniusONE Platform

The nGeniusONE Service Assurance platform provides insights into the performance characteristics of data, voice and video service delivery to manage the availability and quality of the user's experience. nGeniusONE helps dramatically shorten the time required to solve network and application performance issues by providing a common set of metadata for service visibility across network elements, applications and devices to address the needs of network and IT operations teams.

ASI Technology



NETSCOUT's patented, ASI technology is a next generation Deep Packet Inspection (DPI) engine that intelligently and efficiently analyzes packet and flow data to provide real-time, contextual analysis of service, network and application performance. ASI provides an unparalleled wealth of information and uses sophisticated algorithms that determine the best way to process, store and retrieve data, guaranteeing that InfiniStreamNG probes make the most efficient use of compute and storage resources.



Americas East
310 Littleton Road
Westford, MA 01886-4105
USA
Phone: 978-614-4000
Toll Free: 800-357-7666

Americas
3033 W. President
George Bush Hwy
Plano, TX 75075-5752
USA

APAC
238A Thomson Road, #25-04/05
Novena Square Tower A
Singapore 307684

EMEA
One Thames Valley
Wokingham Road
Bracknell, Berkshire
RG42 1NG
UK

NETSCOUT offers sales, support, and services in over 32 countries.

For more information, please visit www.netscout.com or call us at 1-800-833-9200 option 1 or +1 469-330-4000

© 2016 NETSCOUT SYSTEMS, INC. All rights reserved. NETSCOUT, nGenius, InfiniStream, Sniffer, nGeniusONE, ASI, Adaptive Service Intelligence and the NETSCOUT logo are registered or pending trademarks of NETSCOUT SYSTEMS, INC. and/or its affiliates in the United States and/or other countries ("NETSCOUT"). All other brands and product names are registered and unregistered trademarks are the sole property of their respective owners. Use of this product is subject to the NETSCOUT SYSTEMS, INC. ("NETSCOUT") End User License Agreement that accompanies the product at the time of shipment or, if applicable, the legal agreement executed by and between NETSCOUT and the authorized end user of this product ("Agreement"). NETSCOUT reserves the right, at its sole discretion, to make changes at any time in its technical information, specifications, service, and support programs.