

InfiniStreamNG 4800 Appliance

HIGHLIGHTS

- Provides storage capacity of 32 TB per appliance, with extended storage capacity up to 128 TB with a 96 TB ESU
- Hardware and software appliance options
- Supports suite of nGeniusONE® Service Assurance platform and NETSCOUT® Security Analytics applications

InfiniStreamNG Overview

The InfiniStreamNG™ appliance (ISNG) with NETSCOUT's patented Adaptive Service Intelligence™ (ASI) technology efficiently converts packet data into the “smart data” required for contextual views into today's complex networks, applications, and business services.

ISNG hardware and software appliances provide the continuous views into physical, virtual, and hybrid technologies required to improve performance of the applications and networks supporting businesses and their end-users. In addition, ISNG technology allows business and government information technology (IT) teams to consolidate specialized third-party tools and feed NETSCOUT smart data to a wide range of analytics stacks for insights into service assurance, application performance management, cybersecurity, and business intelligence.

NETSCOUT offers multiple ISNG models to support the different processing and storage needs of enterprise, commercial, and government environments, including deployment in data center and remote offices, as well as the network edge. ISNG models can be deployed in tandem for seamless analysis across the entire network, making it easier and more cost-effective to monitor and gather intelligence from multiple sources, with no disruption to business processes.

InfiniStreamNG 4800 Overview

The ISNG 4800 appliance is ideal for high-capacity 1/10 Gigabit monitoring in data centers, high-volume aggregation links, and other environments that require vast storage for long-term, historical forensic analysis.

With an impressive storage capacity that begins at 32 TB, the ISNG 4800 appliance can be expanded all the way to 128 TB per appliance, using a 96 TB extended storage unit (ESU).

Deployment

Strategically deployed throughout the network, ISNG 4800 appliances provide superior processing power, packet capture, and data storage appropriate for high-volume traffic found in the core of large enterprises and data centers. In addition, ISNG 4800 appliances can be deployed alongside other NETSCOUT ASI-based data sources to expand end-to-end visibility into cloud and virtualized environments.



4895 | 32 TB up to 128 TB, 4-Port 1/10 GbE SFP+
ESU | 96 TB, Extended Storage Unit

SPECIFICATIONS

InfiniStreamNG 4800 Hardware Appliance Option

Packet Capture Ports	4-Port 1/10 GbE SFP/SFP+
Management Port	2 RJ-45 1/10GBASE-T1 IPMI 1000BASE-T
Storage	32 TB (RAID 5) up to 128 TB with ESU (RAID 6)
Embedded OS	Solid-State Drive (SSD) dedicated to Linux® OS
Rack Unit	1 Rack Unit (1 RU)
Dimensions	Height: 1.7 in (43 mm) Width: 17.2 in (437 mm) Depth: 25.6 in (650 mm)
Weight	38 lbs. (17.24 kg)
Mounts	Rack mount side rails included
Power Rating (AC)	700W/750W redundant, auto-ranging:700W: 100 – 140 VAC, 50 – 60 Hz, 8.0 – 6 Amp750W: 200 – 240 VAC, 60 – 50 Hz, 4.5 – 3.8 Amp
Maximum Consumption (AC)	5.7A, 586W
Heat Dissipation (AC)	1999 BTU/Hr
Power Rating (DC)	1+1 hot-swappable, redundant-48VDC, 650W, 20A (x2)
Maximum Consumption (DC)	12A, 581W
Heat Dissipation (DC)	1982 BTU/Hr
Vibration	0.25G from 5-200Hz for 15 minutes
Operating Temperature	41° to 95°F (5° to 35°C)
Operating Humidity	8% - 90% (non-condensing)
Altitude	-50 to 10,000 ft (-16 to 3,048 m)
Mechanical Shock	1 shock pulse of 20G for up to 2.5ms
Regulatory Approvals	Regulatory Model Number: NV41U, FCC Part 15 Class A, CE Mark (EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3), VCCI (Japan) Class A, RCM (Australia), RRA (Korea) KC Cert #: KCC-REM-NSZ-NV41U, UL 60950- 1, CAN/CSA C22.2 No. 60950, IEC 60950-1, EN 60950-1, CB Report, UL-GS (DEMKO)

InfiniStreamNG 4800 Software Appliance Option

The ISNG 4800 software appliance provides an option for deploying a customer-provided hardware platform certified to support NETSCOUT ISNG software. With this approach, the NETSCOUT-certified software kit (comprised of ISNG ASI software and an ASI Accelerator NIC) is purchased from NETSCOUT, and a hardware appliance is purchased from NETSCOUT Contract Manufacturing. This certified ISNG 4800 software appliance approach offers 100% performance parity with the ISNG 4800 hardware appliance.

SPECIFICATIONS

ESU (Extended Storage Unit)

Storage	96 TB (RAID 6)
Rack Unit	3-Rack Unit (3 RU)
Dimensions	Height: 5.2 in (132 mm) Width: 17.2 in (437 mm) Depth: 25.5 in (648 mm)
Weight	70.35 lbs. (31.91 kg)
Mounts	Rack mount side rails included
Power Rating (AC)	1+1 hot-swappable, redundant 100-240VAC, 50-60Hz auto-ranging, 900W (12A at 100VAC, 4A at 240VAC)
Maximum Consumption (AC)	2A, 235W
Heat Dissipation (AC)	802 BTU/Hr
Power Rating (DC)	1+1 hot-swappable, redundant 850W, -48VDC, (2x) 24 Amp
Maximum Consumption (DC)	5A, 240W
Heat Dissipation (DC)	819 BTU/Hr
Vibration	0.75G at 5-200Hz
Operating Temperature	50° to 95°F (10° to 35°C)
Operating Humidity	8% - 90% (non-condensing)
Altitude	-45 to 9,500 ft (-13.7m to 2,896 m)
Mechanical Shock	1 shock pulse up to 40G for up to 2ms
Regulatory Approvals	Regulatory Model Number: V3JBD, FCC Part 15 Class A, CE Mark (EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3), VCCI (Japan) Class A, RRA (Korea) KC Cert #: KCC- REM-NSZ-V3JBD UL 60950-1, CAN/CSA C22.2 No. 60950, IEC 60950-1, EN 60950-1, CB Report, UL- GS (DEMKO)

nGeniusONE Platform

nGeniusONE is a real-time information platform that provides a single pane of glass to view the data, voice, and video service delivery performance to manage both the availability and quality of the user's experience.

Available on both hardware and virtual platforms, nGeniusONE leverages NETSCOUT smart data as a universal source for providing smarter analytics for end-to-end visibility throughout private, virtualized, public, and hybrid cloud environments.

ASI Technology



ASI technology transforms packet data into smart data, providing real-time visibility into user experience and offering the most advanced and adaptable information platform for ensuring security, managing risk, and driving service performance.

All ASI-based monitoring platforms are integrated with the nGeniusONE Service Assurance platform to provide a common set of metadata analytics.

LEARN MORE

For more information about ISNG appliance options please visit:

<https://www.netscout.com/product/isng-platform>

NETSCOUT®

Corporate Headquarters

NETSCOUT Systems, Inc.
Westford, MA 01886-4105
Phone: +1 978-614-4000
www.netscout.com

Sales Information

Toll Free US: 800-309-4804
(International numbers below)

Product Support

Toll Free US: 888-357-7667
(International numbers below)

NETSCOUT offers sales, support, and services in over 32 countries. Global addresses, and international numbers are listed on the NETSCOUT website at: www.netscout.com/company/contact-us